



Drying	Thinning & Wash-up	Mesh Range	Stencil Type	Coverage & Mesh	Applications	Fabrics	Colour Range
For optimum fastness PERMASET SUPERCOVER[®] should be heat cured. If drying in the screen, add 1-3% PERMASET[®] Print Retarder .	If necessary, thin with up to 5% water. Dried in ink may be washed out with conventional or eco-friendly screenwash.	Monofilament Polyester. 43-90T (110-225 tpi) depending on application for PERMASET SUPERCOVER[®] colours and PERMASET[®] Metallic colours.	MUST be water resistant, fully dried & fully cured. Emulsion: Recommend: Fujifilm Dirasol [®] 916 or KIWO POLYCOL [®] MULTI-TEX / VERSA-TEX [™] or ULANO [®] 925WR or Chromaline [®] CP-TEX [™] or MacDermid Autotype PLUS 6000 or Murakami TXR [®] /T9.	15-21 m ² /L with 62T mesh. 612-857 square feet per gallon with 155 tpi mesh.	T-Shirts, Flags, Banners, Sports and Fashion Wear. Scarves, Swimwear, Upholstery and Window Furnishings. Yardage, cushions, table and bed linen, tea towels and tote bags.	Cotton. Cotton/Polyester blends and most synthetic fabrics. Fastness to wash and dry cleaning on wool may be diminished.	13 PERMASET SUPERCOVER[®] colours + Black, 2 Whites and Print Paste. 8 PERMASET SUPERCOVER[®] Glow colours and 4 Metallic colours.
Properties Opaque screen printing inks for dark fabrics. Matt Finish. Solvent-free. Low odour. Intermixable, light fast,* non-bleeding colours. PERMASET SUPERCOVER[®] , Glow and Metallic [†] colours exhibit excellent opacity. Soft handle. Excellent wash and dry clean resistance once cured. Ironable.				Product Resistance After heat curing, prints exhibit excellent resistance to wet and dry rub.			

DRYING AND CURING

For optimum wash and colour fastness, prints should be fully heat cured. Whilst the below information is a guide, the curing schedule used should be chosen to suit the heat resistance of the fabric being printed.

Care must be taken with IR dryers to ensure that prints are fully cured. When printing on synthetic blends and fabrics, a lower curing temperature and longer drying time is recommended. If your drying conditions fall outside these recommendations, please contact your local representative for technical assistance.

The following curing guidelines are recommendations for ink deposit temperatures, not dryer temperatures. This should be checked with temperature strips or IR guns to ensure that appropriate temperatures are achieved.

2-3 Minutes @ 160°C (320°F)

5-6 Minutes @ 140°C (285°F)

8-9 Minutes @ 120°C (250°F)

If using **PERMASET[®] Print Retarder** in the ink, note that this will also slow drying in the oven. Ensure that a test wash is completed to confirm that cure regime is adequate.

FASTNESS

Light Fastness is good-excellent. Most colours achieve a rating of 8/8 on the Blue Wool Scale, but all* are not less than 6/8. When fully heat cured, prints have excellent wash and dry clean fastness.

Colour Matches: Note that high temperatures combined with strong detergents can cause colour changes in some colour matches. It is therefore imperative that all formulations are checked for acceptable wash fastness properties prior to production.

* All Glow colours exhibit diminished light fastness, particularly in direct sunlight.

PERMASET, PERMASET SUPERCOVER, PERMATONE and PERMAPRINT PREMIUM are registered or pending trademarks.

PERMASET, PERMASET SUPERCOVER, PERMATONE and PERMAPRINT PREMIUM inks are manufactured by:


colormaker
INDUSTRIES
quality coatings through research & innovation 

44 Orchard Rd Brookvale NSW 2100 Australia
Phone: +61 2 9939 7977 or Fax: +61 2 9939 6685
www.permaset.com.au • email: info@permaset.com.au



ISO 14001 EMS - Environmental Management Systems compliant paper

Scan for stockists.



OPAQUE SCREEN PRINTING INKS FOR DARK FABRICS

SUPERCOVER		SUPERCOVER GLOW*			
Mid Yellow	Rose	Glow Yellow	Glow Green		
Yellow R	Purple	Glow Orange	Glow Blue		
Orange R	Ultra Blue	Glow Red	Glow Violet		
Scarlet	Blue B	Glow Pink	Glow Magenta		
		<th colspan="2">METALLIC†</th>		METALLIC†	
Bright Red	Light Blue				
Mid Red	Green B	Pearl White	Bright Silver		
First Down White	Mid Green	Gold Lustre	Copper		
White	Black				

PERMASET SUPERCOVER[®] Print Paste also available.

*All Glow colours exhibit diminished light fastness, particularly in direct sunlight.

†Metallic colours are part of the PERMASET[®] range.

Colour swatches are a guide only and are as close as printing processes allow. When colour is critical, test printing is essential.